



REF. D.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	LENGTH	
P1 / 24	1	+3.3V	ORANGE	20	JWT	200±16 mm	
	2	+3.3V	ORANGE	20	C4802H02		
	3	COM	BLACK	20	-A80P+ C4802H02		
	4	+5V	RED	20	-A8P+ OR EQUIV		
	5	COM	BLACK	20			
	6	+5V	RED	20			
	7	COM	BLACK	20			
	8	PW-OK	GRAY	24			
	9	+5Vab	PURPLE	20			
	10	+12V8	YELLOW	20			
	11	+12V3	YELLOW	20			
	12	+3.3V	ORANGE	20			
	13	+3.3V	BROWN	24			
	14	-12V	BLUE	24			
	15	COM	BLACK	20			
	16	PS-ON	GREEN	24			
	17	COM	BLACK	20			
	18	COM	BLACK	20			
	19	COM	BLACK	20			
	20						
	21	+5V	RED	20			
	22	+5V	RED	20			
	23	+5V	RED	20			
	24	COM	BLACK	20			
PA	1	+12V2	YELLOW	20	AMP -480484-0 or EQUIV.	250±15 mm	
	2	COM	BLACK	20			
	3	COM	BLACK	20			
	4	+5V	RED	20			
PC	1	+12V2	YELLOW	20	AMP -480484-0 or EQUIV.	310±15 mm	
	2	COM	BLACK	20			
	3	COM	BLACK	20			
	4	+5V	RED	20			
PB	1	+12V2	YELLOW	20	AMP 171822-4 or EQUIV.	150±10 mm	
	2	COM	BLACK	20			
	3	COM	BLACK	20			
	4	+5V	RED	20			
PD	1	+12V2	YELLOW	20	AMP -480484-0 or EQUIV.	150±10 mm	
	2	COM	BLACK	20			
	3	COM	BLACK	20			
	4	+5V	RED	20			
PE	1	COM	BLACK	20	MOLEX 39-01-2040 or EQUIV.	310±15 mm	
	2	COM	BLACK	20			
	3	+12V1	YEL/BLACK	20			
	4	+12V1	YEL/BLACK	20			
PF	1	+12V2	YELLOW	20	CLA27H80 -16P or EQUIV.	310±15 mm	
	2	COM	BLACK	20			
	3	+5V	RED	20			
	4	COM	BLACK	20			
	5	+3.3V	ORANGE	20			
PG	1	+12V2	YELLOW	20	CLA27H80 -16P or EQUIV.	150±10 mm	
	2	COM	BLACK	20			
	3	+5V	RED	20			
	4	COM	BLACK	20			

NOTE:

1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
2. 產地標籤依業務指示加貼.

UNIT:mm

SPI P/N: SPI220LE

MODEL NO. :	SPI220LE	TITLE: ASSY	SHEET: 1 OF 1	REV:01
R&D (2)	PE	DRAWN	DATE	
				July 12, 2007
INTERIOR COUNTERSIGN:			黃鈺婷	