



REF. D.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	LENGTH
P1	1	+3.3V	ORANGE	18	MOLEX 39-01-2240 or EQUIV.	210±16 mm
	2	+3.3V	ORANGE	18		
	3	COM	BLACK	20		
	4	+5V	RED	20		
	5	COM	BLACK	20		
	6	+5V	RED	20		
	7	COM	BLACK	20		
	8	PW-OK	GRAY	22		
	9	+5Veb	PURPLE	22		
	10	+12V2	YELLOW	20		
	11	+12V2	YELLOW	20		
	12	+3.3V	ORANGE	18		
	13	+3.3V	ORANGE	18		
	14	+3.3Vb	BROWN	22		
	15	-12V	BLUE	22		
	16	COM	BLACK	20		
	17	PS-ON	GREEN	22		
	18	COM	BLACK	20		
	19	COM	BLACK	20		
	20	COM	BLACK	20		
	21	+5V	RED	20		
	22	+5V	RED	20		
	23	+5V	RED	20		
	24	COM	BLACK	20		
P2	1	COM	BLACK	20	WST P4-142008 ISB+ P4-142008 X4B OR EQUIV	310±15 mm
	2	COM	BLACK	20		
	3	COM	BLACK	20		
	4	COM	BLACK	20		
	5	+12V1	Yel/Blk	20		
	6	+12V1	Yel/Blk	20		
	7	+12V1	Yel/Blk	20		
	8	+12V1	Yel/Blk	20		
PA	1	+12V2	YELLOW	20	AMP 1-400424-0 or EQUIV.	310±15 mm
	2	COM	BLACK	20		
	3	COM	BLACK	20		
	4	+5V	RED	20		
PB	1	+12V2	YELLOW	20	AMP 1-400424-0 or EQUIV.	150±10 mm
	2	COM	BLACK	20		
	3	COM	BLACK	20		
	4	+5V	RED	20		
PC	1	+5V	RED	22	AMP 171822-4 or EQUIV.	150±10 mm
	2	COM	BLACK	22		
	3	COM	BLACK	22		
	4	+12V2	YELLOW	22		
PD	1	+3.3V	ORANGE	20	CLA27LHS0 -16P or EQUIV.	310±15 mm
	2	COM	BLACK	20		
	3	+5V	RED	20		
	4	COM	BLACK	20		
	5	+12V2	YELLOW	20		
PF	1	+3.3V	ORANGE	20	CLA27GHD0 -16P or EQUIV.	160±10 mm
	2	COM	BLACK	20		
	3	+5V	RED	20		
	4	COM	BLACK	20		
	5	+12V2	YELLOW	20		

NOTE:

1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
2. 產地標籤依業務指示加貼.

UNIT:mm

SPI P/N.:SPI300F4BB
P/N.:9PA300CH02

MODEL NO. : SPI300F4BB		TITLE: ASSY		SHEET: 1 OF 1		REV:02	
R&D(2)		PE		DRAWN		DATE	
(46.26)				Paul		Jun.18.2009	
INTERIOR COUNTERSIGN:							