



Sparkle Power Inc.
 A Leading Power Supply Manufacturer
 Web site: www.sparklepower.com



SPI5102UA

(RoHS Compliant)

510 Watts ATX12V/ EPS12V 2U Switching Power Supply

Features

- Complied with ATX12V/EPS12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer (thermal fan speed control function)
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by : UL,CSA22.2 NO or CUL 60950-1, TUV or VDE, EMC,FCC ,CE, CB report.

Input Characteristics

Input Range: 90 ~ 265Vac , Full Range Input
Frequency: 47 ~ 63Hz
Input Current: Max 10A @ 115Vac, 5A @ 230Vac
Inrush Current: No Damage

Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0.8A	12A	24A	+ 5%-4%	50mV P-P
+5V	0.5A	12.5A	25A	+ 5%-4%	50mV P-P
+12V1	0.0A	9A	18A	+ 5%-4%	120mV P-P
+12V2	1A	9A	18A	+ 5%-4%	120mV P-P
-12V	0.0A	0.25A	0.5A	+ 9%-4%	120mV P-P
+5Vsb	0.1A	1.25A	2.5A	+ 5%-4%	50mV P-P

- *+3.3V and +5V total output not exceed 150W
- *+12V1 and +12V2 total output not exceed 32A
- * Total output for this subject power supply is 510W

Sparkle Power Inc.
Main Office
 1000 Rock Avenue
 San Jose, CA 95131
 TEL: 408-519-8888
 FAX: 408-519-9999
 E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
 17071 Green Drive
 City of Industry, CA 91745
 TEL: 626-839-7180
 FAX: 626-839-3395

Specification

- **Temperature Range:** Operating: 0°C ~ +50°C on full load; De-rate 3W/°C from 40°C to 50°C; storage & shipping:20°C ~ +80°C
- **Humidity:** 5%- 95% on operating,5%- 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency:** 70% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise time:** Less than 50ms
- **Hold-up Time:** 18 ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 240x100x70mm /9.5x3.9x 2.7 inch