

# Redundant

## Mini Redundant

Dimension(L\*W\*H): 190\*150\*84 (mm)

Mini Redundant



Model	Watts	+3.3V	+5V	+12V1	+12V2	+12V3	-12V	+5Vsb	-5V	Input Voltage	Safety	
SPR2CA3508	350W	Min	0.5A	0.5A	0.5A	0.5A	0.5A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	20A	20A	18A	18A	14A	0.8A	2A	0.5A		
(1)+3.3V&+5V total output not exceed 100W (2)Total DC output is 350W												
SPR2CA4508	450W	Min	0.5A	0.5A	0.5A	0.5A	0.5A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	20A	20A	18A	18A	16A	0.8A	2A	0.5A		
(1)+3.3V&+5V total output not exceed 100W (2)Total DC output is 450W												
SPR2CA5008	500W	Min	0.5A	0.5A	0.5A	0.5A	0.5A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	20A	20A	19A	19A	18A	0.5A	2.0A	0.5A		
(1)+3.3V&+5V total output not exceed 100W (2)Total DC output is 500W												

## 2U Redundant

Dimension(L\*W\*H): 300\*101\*84 (mm)

2U Redundant



Model	Watts	+3.3V	+5V	+12V1	+12V2	+12V3	-12V	+5Vsb	-5V	Input Voltage	Safety	
SPR2C350	350W	Min	0.5A	0.5A	0.5A	0.5A	1A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	20A	25A	15A	15A	15A	0.5A	2A	0.2A		
(1)+3.3V&+5V total output not exceed 150W (2)Total DC output is 350W												
SPR2C520	520W	Min	0.5A	0.5A	0.5A	0.5A	1A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	24A	25A	15A	15A	15A	0.5A	2A	0.2A		
(1)+3.3V&+5V total output not exceed 150W (2)Total DC output is 520W												
SPR2C620	620W	Min	0.5A	0.5A	0.5A	0.5A	1A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	24A	25A	16A	16A	16A	0.5A	2A	0.2A		
(1)+3.3V&+5V total output not exceed 150W (2)Total DC output is 620W												
SPR2C700	700W	Min	0.5A	0.5A	0.5A	0.5A	1A	0A	0A	0A	Full Range	UL/CUL, FCC, TUV, CB, CE
		Max	24A	30A	18A	18A	18A	0.5A	3A	0.2A		
(1)+3.3V&+5V total output not exceed 170W (2)Total DC output is 700W												