



Sparkle Power Inc.
A Leading Power Supply Manufacturer
Web site: www.sparklepower.com

SUPER350 (SP350PN)

(RoHS Compliant)

350 Watts ATX12V 2.2 Switching Power Supply

Features

- Complied with ATX12V standard
- High efficiency and reliability
- Remote ON/OFF function
- Internal 12V DC fan included
- Super quiet with 12cm big Fan
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart B/Sep.2005
- Approved by UL/CUL 60950-1, FCC

Input Characteristics

Input Range: 115 ~ 230Vac (RMS), manual selection
Frequency: 47 ~ 63Hz
Input Current: Max 8A (RMS) @ 115Vac, 4A (RMS) @ 230Vac
Inrush Current: No damage.

Output Characteristics

| Output Voltage | Minimum Load | Normal Load | Maximum Load | Load Reg. | Line Reg. | Ripple & Noise |
|----------------|--------------|-------------|--------------|-----------|-----------|----------------|
| +3.3V | 0.5A | 11A | 22.0A | ± 5% | ± 1% | 50mV P-P |
| +5V | 0.3A | 10.5A | 21.0A | ± 5% | ± 1% | 50mV P-P |
| +12V1 | 1.0A | 5.0A | 18.0A | ± 5% | ± 1% | 120mV P-P |
| +12V2 | 1.0A | 7.5A | 16.0A | ± 5% | ± 1% | 120mV P-P |
| -12V | 0.0A | 0.15A | 0.3A | ± 10% | ± 2% | 120mV P-P |
| +5Vsb | 0.0A | 1.0A | 2.5A | ± 5% | ± 1% | 50mV P-P |

*+3.3V and +5V total output not exceed 130W

*+3.3V and +5V and +12V1 +12V2 total output not exceed 335W.

* Total output for this subject power supply is 350W

Sparkle Power Inc.
Main Office
1000 Rock Avenue
San Jose, CA 95131
TEL: 408-519-8888
FAX: 408-519-9999
E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
17071 Green Drive
City of Industry, CA 91745
TEL: 626-839-7180
FAX: 626-839-3395



Specification

- **Temperature Range:** Operating: 0°C ~ +50°C ,Full load at 25°C ; De-rate 2W/°C from 25°C to 50 °C ,storage & shipping: -20°C ~ +65°C
- **Humidity:** 90% on operating,95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency:** 70% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA.
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 140x150x86mm / 5.5x6x3.4inch

