

Specifications

Model	SPU-600	SPU-800
Capacity	600VA/360W	800VA/480W
INPUT		
Power Factor value	0.8	
Voltage	110/120VAC	
Voltage Range	85-145VAC	
OUTPUT		
Voltage	110/120VAC	
AC Voltage Regulation (Battery Mode)	±10%	
Frequency Range (Battery Mode)	50Hz or 60Hz ± 1 Hz	
Transfer Time	Typical 2-6ms, 10ms max.	
Waveform (Battery Mode)	Simulated Sine Wave	
Output connector	Nema x 4	
BATTERY		
Battery Type & Number	12V/7Ah x 1	12V/9AH x 1
Typical Recharge Time	4 hours recover to 90% capacity	
INDICATORS		
AC Mode	Green lighting	
Battery Mode	Green flashing	
ALARM		
Battery Mode	Sounding every 10 seconds	
Low Battery	Sounding every second	
Overload	Sounding every 0.5 second	
Battery Replacement	Sounding every 2 seconds	
Fault	Continuously sounding	
PHYSICAL		
Dimension, DXWXH (mm)	330 x 100 x 140	
Net Weight (kgs)	6	6.6
ENVIRONMENT		
Humidity	0-90% RH @ 0- 40°C (non-condensing)	
Noise Level	Less than 40dB	
INTERFACE		
USB Port (option)	Supports Windows® 98/2000/XP/Vista/ Windows® 7, Linux, and MAC	
RJ-11 (option)	Modem/phone surge protection	
Equipment protection policy	2 years warranty (Battery warranty for 1 year)	

* Product specifications are subject to change without further notice